

## **354 Series Single Stage Bulb & Capillary Thermostats**

## **Cross Reference**

- Widest Calibration Temperature range available on the market.
- Maximum ambient temperature of 250°F.
- Senasys bulb & capillary thermostats are proudly designed & manufactured in Eau Claire, WI, U.S.A.



Features	354 Single Stage Bulb & Capillary Thermostats Cross Reference Product Details			
	Senasys	PECO Controls	Robertshaw	E.G.O.
-40°F to 675°F Temperature Range	354 Series	T103 Series	C1, B10 or K & 5 Series	EF Series
Fixed or Adjustable Setting	~	Х	~	~
D-Shaft Adjustment	~	~	<b>~</b>	<b>~</b>
250°F Maximum Ambient Temperature	~	Х	Х	<b>~</b>
Automatic Reset Configuration	~	~	~	~
Screw Terminals	~	~	~	~
Wire Lead Options Available	~	X	<b>~</b>	X
Rated 25A @ 250VAC (+100,000 cyles)	~	X	<b>~</b>	X
Single-pole, single throw (SPST), or Single-pole, double-throw (SPDT)	~	~	<b>~</b>	<b>~</b>
Copper or Stainless Steel Bulb & Capillary Material Options	~	<b>~</b>	<b>~</b>	<b>~</b>
UL / cUL Approved	~	~	<b>~</b>	<b>~</b>
Made in U.S.A.	~	X	X	X

